

**IN THE CLAIMS:**

1. (Original) A disk holder comprising:

a plurality of holder plates that individually hold a plurality of disks, and  
a plurality of disk holding mechanisms with which the holder plates are provided,

wherein

5 the disk holding mechanism comprises a disk hold link that comprises a catch that  
engages with and disengages from the center hole of the disk..

2. (Original) The disk holder according to claim 1, wherein

at least a pair of the disk hold links is provided so as to be able to turn in the  
direction of engagement with and disengagement from the disk center hole about a common axis;

5 a disk hold arm for allowing the disk hold link to turn is provided so as to be able  
to perform a sliding movement in the radial direction of the disk; and

a depressed portion that is biased by an external force is provided in the vicinity  
of the outer edge of the disk of the disk hold arm.

3. (Original) The disk holder according to claim 1 or 2, wherein a hole is formed in

10 a position corresponding with the center hole of the disk in the holder plate; and the disk hold  
link is installed in the hole.

4. (Original) The disk holder according to any one of claims 1 to 3, wherein

the holder plate is substantially fan-shaped, and the arc of the holder plate is  
shorter than a semi-circle of the disk.

5. (Original) A disk drive, comprising the disk holder according to any one of  
15 claims 1 to 4, wherein

a plurality of the holder plate in the disk holder are arranged stacked such that  
each holder plate can be individually raised and lowered,

the disk drive further comprising:

a drive unit for playing back a desired disk;

20 a disk selector that forms a space above and below the desired disk by raising and  
lowering a holder plate in the disk holder; and

drive moving means for moving the drive unit into the space formed as a result of  
raising and lowering the holder plate.

6. (Original) The disk drive according to claim 5, wherein  
25 disk grasping means for grasping and releasing the desired disk is provided in  
sync with the engagement and disengagement of the catch of the disk hold link when the holder  
plate is raised and lowered by the disk selector.

7.-19. (Cancelled)